



HG-240S/245S/
250S/255S



HIMIN CLEAN ENERGY HOLDINGS CO.,LTD.

Monocrystalline photovoltaic module



MONOCRYSTALLINE SILICON PHOTOVOLTAIC MODULE WITH 240W~255W POWER

Himin Clean Energy Holdings Co., Ltd, as the main holder of the fourth International Solar City Congress (Dezhou city, 2010) and the constructor of China Solar Valley, has concentrated on solar energy research since 1995.

Himin's HG-240S~255S photovoltaic module is designed for large electrical power requirements, this module has super durability to withstand rigorous operating conditions and is suitable for grid connected systems.

Quality & Reliability

Robust, corrosion resistant aluminum frames independently tested to withstand wind loads of up to 2400Pa and snow loads of up to 5400Pa ensuring a stable mechanical life.

Module independently tested to ensure conformances with certification and regulatory standards.

Manufacturing factory certified by ISO9001 and ISO14001.


Guarantees and certifications

Product warranty	10 years
Performance guarantee	Guaranteed output of 90% for 10 years and 80% for 25 years
Approvals and certificates	TUV:IEC 61215 Edition II, IEC 61730 I and II, MCS

In the absence of confirmation by specification sheets, Himin takes no responsibility for any defects that any occur in the equipment using any Himin products shown in catalogs, data books, etc.

Contact Himin in order to obtain the latest specification sheets, before using any Himin products.

Specifications are subject to change without notice.



Specifications


HG-240S~255S

Cell	Monocrystalline silicon solar cells, 156mm square
Number of cells and connections	60 in series
Application	DC 24V system
Maximum system voltage	DC 1,000V
Series fuse rating	15A
Nominal power	240W~255W
Dimensions	1640×992×50mm
Weight	19.6Kg
Type of output terminal	Lead wire with connectors
Junction box	3 bypass diodes

Electro-optical characteristics

Parameters	Symbol	HG-240S	HG-245S	HG-250S	HG-255S
Open circuit voltage	Voc	37.4V	37.4V	37.6V	37.7V
Maximum power voltage	Vmp	30.5V	30.7V	31.0V	31.4V
Short circuit current	Isc	8.66A	8.67A	8.68A	8.71A
Maximum power current	Imp	7.87A	7.98A	8.06A	8.12A
Maximum power	Pm	240W	245W	250W	255W
Encapsulated solar cell efficiency	η_c	16.8%	17.0%	17.4%	17.8%
Module efficiency	η_m	14.8%	15.1%	15.4%	15.7%
Power output tolerance		0~3%	0~3%	0~3%	0~3%

Characteristics



Packaging Specifications

Number of modules per pallet	46
Number of pallets per 40' container	11
Packaging box dimensions (L / W / H)	2260×1020×2160mm
Box weight	942Kg

Conditions

Standard test conditions (STC)

Irradiance: 1,000W/m²


AM1.5

Module temperature: 25°C

Temperature coefficients

Parameters	Rating
Operating temperature	-40 to +85°C
Storage temperature	-40 to +85°C
α Pm	-0.470%/K
α Isc	+0.036%/K
α Voc	-0.346%/K
NOCT	46 ± 2/ °C

Outline dimensions



Mechanical specification

Cable	Solar cable, 900mm length 4mm ² prefabricated with plugs (male/female)
Front glass	Transparent toughened safety glass, 3.2mm
Cell encapsulation	EVA (Ethylene-Vinyl-Acetate), 0.5mm
Backside	Composite film
Frame	Anodised aluminium cavity frame
Maximum surface load	(screwless) with drainage holes Entire module certified to withstand high wind loads (2400Pa) snow loads (5400Pa)
Hail resistance	Maximum diameter of 25mm with impact speed 83km/h